



G50WDO-3A-T4F



Model	G50WDO-3A-T4F		
PRIME POWER RATING	AMPS	KW	KVA
@ 480V-3Ø, 0.8PF, 60Hz	58	38	48
@ 240V-3Ø, 0.8PF, 60Hz	115	38	48
@ 208V-3Ø, 0.8PF, 60Hz	125	36	45
@ 240V-1Ø, 1.0PF, 60Hz	140	33.6	33.6
@ 120V-1Ø, 1.0PF, 60Hz	140 × 2	33.6	33.6
@ 400V-3Ø, 0.8PF, 50Hz	58	32	40
Voltage Configuration	3-Position Switch		
Frequency Capability	50Hz/60Hz Switchable		
ENGINE			
Engine Make / Model	Doosan D24		
Displacement (L)	2.392		
Number of Cylinders	4		
Power Output @ 1800RPM - HP (kWm)	59.8 (44.6)		
Emissions Tier Level	Tier 4 Final		
Aftertreatment Technology	DOC		
Usable Fuel Tank Capacity - Gal (L)	110 (416)		
Diesel Exhaust Fluid (DEF) Capacity - Gal (L)	N/A		
Runtime @ 100% Load - Hr	37.2		
DIMENSIONS WITH RUNNING GEAR			
Length - in (mm)	130.5 (3315)		
Width - in (mm)	72.8 (1850)		
Height - in (mm)	78.4 (1992)		
Weight (Ready to Run) - lb (kg)	3870 (1755)		
Sound Level @ 23 ft (7m) and 100%	64		

