


Diesel Generator Set Model DGHE 60 Hz

**50 kW, 62.5 kVA Standby
45 kW, 56 kVA Prime**



Description

The Cummins Power Generation DG-series commercial generator set is a fully integrated power generation system providing optimum performance, reliability, and versatility for stationary standby or prime power applications.

A primary feature of the DG GenSet is strong motor-starting capability and fast recovery from transient load changes. The torque-matched system includes a heavy-duty Cummins 4-cycle diesel engine, an AC alternator with high motor-starting kVA capacity, and an electronic voltage regulator with three phase sensing for precise regulation under steady-state or transient loads. The DG GenSet accepts 100% of the nameplate standby rating in one step, in compliance with NFPA 110 Level 1 requirements.

The standard PowerCommand[®] digital electronic control is an integrated system that combines engine and alternator controls for high reliability and optimum GenSet performance.

Optional weather-protective enclosures and coolant heaters shield the generator set from extreme operating conditions. Environmental concerns are addressed by low emission engines, sound-attenuated enclosures, exhaust silencers, and dual-wall fuel tanks. A wide range of options, accessories, and services are available, allowing configuration to your specific power generation needs.

Every production unit is factory tested at rated load and power factor. This testing includes demonstration of rated power and single-step rated load pickup. Cummins Power Generation manufacturing facilities are registered to ISO9001 quality standards, emphasizing our commitment to high quality in the design, manufacture, and support of our products. The generator set is CSA certified and is available as UL2200 Listed. The PowerCommand control is UL508 Listed.

All Cummins Power Generation systems are backed by a comprehensive warranty program and supported by a worldwide network of 170 distributors and service branches to assist with warranty, service, parts, and planned maintenance support.

Features

UL Listed Generator Set - The complete generator set assembly is available Listed to UL 2200.

Cummins Heavy-Duty Engine - Rugged 4-cycle industrial diesel engine delivers reliable power, low emissions, and fast response to load changes.

Alternator - Several alternator sizes offer selectable motor-starting capability with low reactance 2/3 pitch windings, low waveform distortion with non-linear loads, fault-clearing short-circuit capability, and class H insulation. The alternator electrical insulation system is UL1446 Recognized.

Control Systems - The PowerCommand electronic control is standard equipment and provides total genset system integration, including automatic remote starting/stopping, precise frequency and voltage regulation, alarm and status message display, AmpSentry[™] protection, output metering, auto-shutdown at fault detection, and NFPA 110 Level 1 compliance. PowerCommand control is Listed to UL508.

Cooling System - Standard cooling package provides reliable running at the rated power level, at up to 50°C ambient temperature.

Integral Vibration Isolation - Robust skid base supports the engine, alternator, and radiator on isolators, minimizing transmitted vibration.

E-Coat Finish - Dual electro-deposition paint system provides high resistance to scratching, corrosion, and fading.

Enclosures - Optional weather-protective enclosures are available.

Fuel Tanks - Dual wall sub-base fuel tanks and in-skid day tanks are also offered.

Certifications - Generator sets are designed, manufactured, tested, and certified to relevant UL, NFPA, ISO, IEC, and CSA standards.

Warranty and Service - Backed by a comprehensive warranty and worldwide distributor service network.

Generator Set

The general specifications provide representative configuration details. Consult the outline drawing for installation design.

Specifications – General

See outline drawing 500-3426 for installation design specifications.

Unit Width, in (mm)	40.0 (1016)
Unit Height, in (mm)	48.4 (1229)
Unit Length, in (mm)	82.8 (2104)
Unit Dry Weight, lb (kg)	1584 (719)
Unit Wet Weight, lb (kg)	1603 (727)
Rated Speed, rpm	1800
Voltage Regulation, No Load to Full Load	±1.0%
Random Voltage Variation	±1.0%
Frequency Regulation	5%
Random Frequency Variation	±0.5% (Isochronous optional ±0.25%)
Radio Frequency Interference	Meets requirements of most industrial and commercial applications

Cooling	Standby	Prime
Fan Load, HP (kW)	2.2 (1.6)	2.2 (1.6)
Coolant Capacity with radiator, US Gal (L)	4.0 (15.1)	4.0 (15.1)
Coolant Flow Rate, Gal/min (L/min)	23.0 (87.1)	23.0 (87.1)
Heat Rejection To Coolant, Btu/min (MJ/min)	1965.0 (2.1)	1725.0 (1.8)
Heat Radiated To Room, Btu/min (MJ/min)	800.0 (0.8)	700.0 (0.7)
Maximum Coolant Friction Head, psi (kPa)	5.0 (34.5)	5.0 (34.5)
Maximum Coolant Static Head, ft (m)	26.0 (7.9)	26.0 (7.9)

Air		
Combustion Air, scfm (m ³ /min)	136.0 (3.8)	130.0 (3.7)
Alternator Cooling Air, scfm (m ³ /min)	635.0 (18.0)	635.0 (18.0)
Radiator Cooling Air, scfm (m ³ /min)	3000.0 (84.9)	3000.0 (84.9)
Max. Static Restriction, in H ₂ O (Pa)	0.50 (124.50)	0.50 (124.50)

Rating Definitions

Standby Rating based on: Applicable for supplying emergency power for the duration of normal power interruption. No sustained overload capability is available for this rating. (Equivalent to Fuel Stop Power in accordance with ISO3046, AS2789, DIN6271 and BS5514). Nominally rated.

Prime (Unlimited Running Time) Rating based on: Applicable for supplying power in lieu of commercially purchased power. Prime power is the maximum power available at a variable load for an unlimited number of hours. A 10% overload capability is available for limited time. (Equivalent to Prime Power in accordance with ISO8528 and Overload Power in accordance with ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.

Base Load (Continuous) Rating based on: Applicable for supplying power continuously to a constant load up to the full output rating for unlimited hours. No sustained overload capability is available for this rating. Consult authorized distributor for rating. (Equivalent to Continuous Power in accordance with ISO8528, ISO3046, AS2789, DIN6271, and BS5514). This rating is not applicable to all generator set models.

Site Derating Factors

Engine power available up to 247 m (810 ft), 29.4°C (85°F). Derate at 3% per 305 m (1000 ft) above 247 m (810 ft), 1% per 5.6°C (10°F) above 29.4°C (85°F).

Engine

Cummins heavy-duty diesel engines use advanced combustion technology for reliable and stable power, low emissions, and fast response to sudden load changes.

Mechanical governing is standard. Electronic governing is available for applications requiring constant (isochronous) frequency regulation such as Uninterruptible Power Supply (UPS) systems, non-linear loads, or sensitive electronic loads. Optional coolant heaters are recommended for all emergency standby installations or for any application requiring fast load acceptance after start-up.

Specifications – Engine

Base Engine	Cummins, Inc Model 4BT3.3-G2, Turbocharged, diesel-fueled
Displacement in³ (L)	199.0 (3.3)
Overspeed Limit, rpm	2100 ±50
Regenerative Power, kW	8.50
Cylinder Block Configuration	Cast iron, In-line 4 cylinder
Battery Capacity	200 amps minimum at ambient temperature of 32°F (0°C)
Battery Charging Alternator	35 amps
Starting Voltage	12-volt, negative ground
Lube Oil Filter Types	Single spin-on canister-combination full flow with bypass
Standard Cooling System	104°F (40°C) ambient radiator

Power Output		Standby		Prime					
Gross Engine Power Output, bhp (kWm)		82.0 (61.2)		72.0 (53.7)					
BMEP at Rated Load, psi (kPa)		175.0 (1206.6)		153.0 (1054.9)					
Bore, in. (mm)		3.74 (95.0)		3.74 (95.0)					
Stroke, in. (mm)		4.53 (115.1)		4.53 (115.1)					
Piston Speed, ft/min (m/s)		1359.0 (6.9)		1359.0 (6.9)					
Compression Ratio		17.0:1		17.0:1					
Lube Oil Capacity, qt. (L)		8.4 (7.9)		8.4 (7.9)					
Fuel Flow									
Fuel Flow at Rated Load, US Gal/hr (L/hr)		15.6 (59.0)		15.6 (59.0)					
Maximum Inlet Restriction, in. Hg (mm Hg)		2.9 (73.7)		2.9 (73.7)					
Maximum Return Restriction, in. Hg (mm Hg)		15.0 (381.0)		15.0 (381.0)					
Air Cleaner									
Maximum Air Cleaner Restriction, in. H ₂ O (kPa)		25.0 (6.2)		25.0 (6.2)					
Exhaust									
Exhaust Flow at Rated Load, cfm (m ³ /min)		358.0 (10.1)		326.0 (9.2)					
Exhaust Temperature, °F (°C)		950.0 (510.0)		935.0 (501.7)					
Max Back Pressure, in. H ₂ O (kPa)		41.0 (10.2)		41.0 (10.2)					
Fuel System		Zexel In-Line Direct Injection							
Fuel Consumption		Standby				Prime			
60 Hz Ratings, kW (kVA)		50 (62.5)				45 (56)			
	Load	1/4	1/2	3/4	Full	1/4	1/2	3/4	Full
	US Gal/hr	1.3	2.1	2.9	3.9	1.2	1.9	2.6	3.5
	L/hr	5	8	11	15	4	7	10	13

Alternator

Several alternators are available for application flexibility based on the required motor-starting kVA and other requirements. Larger alternator sizes have lower temperature rise for longer life of the alternator insulation system. In addition, larger alternator sizes can provide a cost-effective use of engine power in across-the-line motor-starting applications and can be used to minimize voltage waveform distortion caused by non-linear loads.

Single-bearing alternators couple directly to the engine flywheel with flexible discs for drivetrain reliability and durability. No gear reducers or speed changers are used. Two-thirds pitch windings eliminate third-order harmonic content of the AC voltage waveform and provide the standardization desired for paralleling of generator sets. The standard excitation system is a self (shunt) excited system with the voltage regulator powered directly from the generator set output.

Alternator Application Notes

Separately Excited Permanent Magnet Generator (PMG) System - This option uses an integral PMG to supply power to the voltage regulator. A PMG system generally has better motor-starting performance, lower voltage dip upon load application, and better immunity from problems with harmonics in the main alternator output induced by non-linear loads. This option is recommended for use in applications that have large transient loads, sensitive electronic loads (especially UPS applications), harmonic content, or that require sustained short-circuit current (sustained 3-phase short circuit current at approximately 3 times rated for 10 seconds).

Alternator Sizes - On any given model, various alternator sizes are available to meet individual application needs. Alternator sizes are differentiated by maximum winding temperature rise, at the generator set standby or prime rating, when operated in a 40°C ambient environment. Available temperature rises range from 80°C to 150°C. Not all temperature rise selections are available on all models. Lower temperature rise is accomplished using larger alternators at lower current density. Lower temperature rise alternators have higher motor-starting kVA, lower voltage dip upon load application, and they are generally recommended to limit voltage distortion and heating due to harmonics induced by non-linear loads.

Alternator Space Heater - is recommended to inhibit condensation.

Available Output Voltages

Three Phase Reconnectable

120/208
 127/220
 139/240
 120/240
 240/416
 254/440
 277/480

Single Phase Non-Reconnectable

120/240

Three Phase Non-Reconnectable

220/380
 347/600

Specifications – Alternator

Design	Brushless, 4 pole, drip proof revolving field
Stator	2/3 pitch
Rotor	Direct coupled by flexible disc
Insulation System	Class H per NEMA MG1-1.65
Standard Temperature Rise	150°C Standby
Exciter Type	Shunt
Phase Rotation	A (U), B (V), C (W)
Alternator Cooling	Direct drive centrifugal blower
AC Waveform Total Harmonic Distortion	<5% total no load to full linear load <3% for any single harmonic
Telephone Influence Factor (TIF)	<50 per NEMA MG1-22.43
Telephone Harmonic Factor (THF)	<3

Three Phase Table¹		105° C	105° C	105° C	105° C	125° C	125° C	125° C	125° C	150° C	150° C	150° C	
Feature Code		B418	B415	B268	B304	B417	B414	B267	B303	B416	B413	B419	
Alternator Data Sheet Number		203	203	204	203	202	203	204	202	202	202	202	
Voltage Ranges		110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	120/208 Thru 139/240 240/416 Thru 277/480	347/600	110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	120/208 Thru 139/240 240/416 Thru 277/480	347/600	110/190 Thru 120/208 220/380 Thru 240/416	120/208 Thru 139/240 240/416 Thru 277/480	347/600	
Surge kW		53.1	53	54.1	53.7	52.2	53	54.1	53	52.2	52.1	53	
Motor Starting kVA (at 90% sustained voltage)	Shunt	188	188	231	188	163	188	231	163	163	163	163	
	PMG	221	221	272	221	191	221	272	191	191	191	191	
Full Load Current - Amps at Standby Rating		<u>120/208</u> 173	<u>127/220</u> 164	<u>139/240</u> 150	<u>220/380</u> 95	<u>240/416</u> 87	<u>277/480</u> 75	<u>347/600</u> 60					

Notes:


1. Single phase power can be taken from a three phase generator set at up to 2/3 set rated 3-phase kW at 1.0 power factor. Also see Note 2 below.

Single Phase Table		105° C	105° C	105° C	105° C	125° C	125° C	125° C	125° C				
Feature Code		B418	B415	B274	B268	B417	B414	B273	B267				
Alternator Data Sheet Number		203	203	204	204	202	203	203	204				
Voltage Ranges		120/240 ¹	120/240 ¹	120/240 ²	120/240 ²	120/240 ¹	120/240 ¹	120/240 ²	120/240 ²				
Surge kW		50.1	51.2	53.6	52.2	49.5	50.8	52.4	52.2				
Motor Starting kVA (at 90% sustained voltage)	Shunt	113	113	130	130	95	113	113	130				
	PMG	133	133	153	153	112	133	133	153				
Full Load Current - Amps at Standby Rating		<u>120/240¹</u> 139	<u>120/240²</u> 208										

Notes:

1. The broad range alternators can supply single phase output up to 2/3 set rated 3-phase kW at 1.0 power factor.
2. The extended stack (full single phase output) and 4 lead alternators can supply single phase output up to full set rated 3-phase kW at 1.0 power factor.

Control System

	<p>PowerCommand Control with AmpSentry™ Protection</p> <ul style="list-style-type: none"> • The PowerCommand Control is an integrated generator set control system providing governing, voltage regulation, engine protection, and operator interface functions. • PowerCommand Controls include integral AmpSentry protection. AmpSentry provides a full range of alternator protection functions that are matched to the alternator provided. • Controls provided include Battery monitoring and testing features, and Smart-Starting control system. • InPower PC-based service tool available for detailed diagnostics. • Available with Echelon LonWorks™ network interface. • NEMA 3R enclosure. • Suitable for operation in ambient temperatures from -40C to +70C, and altitudes to 13,000 feet (5000 meters). • Prototype tested; UL, CSA, and CE compliant. 	
<p>AmpSentry AC Protection</p> <ul style="list-style-type: none"> • Overcurrent and short circuit shutdown • Overcurrent warning • Single & 3-phase fault regulation • Over and under voltage shutdown • Over and under frequency shutdown • Overload warning with alarm contact • Reverse power and reverse Var shutdown • Excitation fault 	<p>Engine Protection</p> <ul style="list-style-type: none"> • Overspeed shutdown • Low oil pressure warning and shutdown • High coolant temperature warning and shutdown • High oil temperature warning (optional) • Low coolant level warning or shutdown • Low coolant temperature warning • High and low battery voltage warning • Weak battery warning • Dead battery shutdown • Fail to start (overcrank) shutdown • Fail to crank shutdown • Redundant start disconnect • Cranking lockout • Sensor failure indication 	<p>Operator Interface</p> <ul style="list-style-type: none"> • OFF/MANUAL/AUTO mode switch • MANUAL RUN/STOP switch • Panel lamp test switch • Emergency Stop switch • Alpha-numeric display with pushbutton access, for viewing engine and alternator data and providing setup, controls, and adjustments • LED lamps indicating genset running, not in auto, common warning, common shutdown • (5) configurable LED lamps • LED Bargraph AC data display (optional)
<p>Alternator Data</p> <ul style="list-style-type: none"> • Line-to-line and line-to-neutral AC volts • 3-phase AC current • Frequency • Total and individual phase kW and kVA 	<p>Engine Data</p> <ul style="list-style-type: none"> • DC voltage • Lube oil pressure • Coolant temperature • Lube oil temperature (optional) 	<p>Other Data</p> <ul style="list-style-type: none"> • Genset model data • Start attempts, starts, running hours • KW hours (total and since reset) • Fault history • Load profile (hours less than 30% and hours more than 90% load) • System data display (optional with network and other PowerCommand gensets or transfer switches)
<p>Governing</p> <ul style="list-style-type: none"> • Integrated digital electronic isochronous governor • Temperature dynamic governing • Smart idle speed mode • Glow plug control (some models) 	<p>Voltage Regulation</p> <ul style="list-style-type: none"> • Integrated digital electronic voltage regulator • 3-phase line to neutral sensing • PMG (Optional) • Single and three phase fault regulation • Configurable torque matching 	<p>Control Functions</p> <ul style="list-style-type: none"> • Data logging on faults • Fault simulation (requires InPower) • Time delay start and cooldown • Cycle cranking • (4) Configurable customer inputs • (4) Configurable customer outputs • (8) Configurable network inputs and (16) outputs (with optional network)
<p>Options</p>		
<ul style="list-style-type: none"> <input type="checkbox"/> Power Transfer Control <input type="checkbox"/> Analog AC Meter Display <input type="checkbox"/> Thermostatically Controlled Space Heater 	<ul style="list-style-type: none"> <input type="checkbox"/> Key-type mode switch <input type="checkbox"/> Ground fault module <input type="checkbox"/> Engine oil temperature <input type="checkbox"/> Auxilliary Relays (3) 	<ul style="list-style-type: none"> <input type="checkbox"/> Echelon LonWorks interface <input type="checkbox"/> Digital input and output module(s) (loose) <input type="checkbox"/> Remote annunciator (loose)

Generator Set Options

Engine

- 120/240 V, 1000 W coolant heaters
- 120/240 V, 150 W lube oil heater
- Electronic governor

Cooling System

- 125°F (50°C) ambient cooling
- Remote radiator cooling

Fuel System

- 12 hour dual wall sub-base tank
- 24 hour dual wall sub-base tank
- Single wall sub-base tank, 80 gal
- In-skid tank, 44 gal

Alternator

- 105°C rise alternator
- 125°C rise alternator
- 120/240 V, 100 W anti-condensation heater
- Extended stack (full single phase output)
- PMG excitation
- Single phase

Exhaust System

- GenSet mounted muffler
- Heavy duty exhaust elbow
- Slip on exhaust connection

Generator Set

- AC entrance box
- Batteries
- Battery charger
- Export box packaging
- UL2200 Listed
- Main line circuit breaker
- PowerCommand Network Communication Module (NCM)
- QuietSite Level 1 enclosure w/silencer
- QuietSite Level 2 enclosure w/silencer
- Aluminum enclosures
- Remote annunciator panel
- Spring isolators
- Weather protective enclosure with silencer
- 2 year prime power warranty
- 2 year standby warranty
- 5 year basic power warranty

Available Products and Services

A wide range of products and services is available to match your power generation system requirements. Cummins Power Generation products and services include:

Diesel and Spark-Ignited Generator Sets

Transfer Switches

Bypass Switches

Parallel Load Transfer Equipment

Digital Paralleling Switchgear

PowerCommand Network and Software

Distributor Application Support

Planned Maintenance Agreements

Warranty

All components and subsystems are covered by an express limited one-year warranty. Other optional and extended factory warranties and local distributor maintenance agreements are available. Contact your distributor/dealer for more information.

Certifications



ISO9001 - This generator set was designed and manufactured in facilities certified to ISO9001.



CSA - This generator set is CSA certified to product class 4215-01.



PTS - The Prototype Test Support (PTS) program verifies the performance integrity of the generator set design. Products bearing the PTS symbol have been subjected to demanding tests in accordance to NFPA 110 Level 1 to verify the design integrity and performance under both normal and abnormal operating conditions including short circuit, endurance, temperature rise, torsional vibration, and transient response, including full load pickup.



UL - The generator set is available Listed to UL 2200, Stationary Engine Generator Assemblies. The PowerCommand control is Listed to UL 508 - Category NITW7 for U.S. and Canadian usage.

See your distributor for more information



Cummins Power Generation
1400 73rd Avenue N.E.
Minneapolis, MN 55432
763.574.5000
Fax: 763.574.5298
www.cumminspower.com

Cummins and PowerCommand are registered trademarks of Cummins Inc.
AmpSentry is a trademark of Cummins Inc.
LonWorks is a registered trademark of Echelon

Important: Backfeed to a utility system can cause electrocution and/or property damage. Do not connect generator sets to any building electrical system except through an approved device or after building main switch is open.