


## Standard Features

- Your Spectrum® product distributor provides one-source responsibility for the generating system and accessories.
- The generator set and its components are prototype-tested, factory-built, and production-tested.
- The generator set provides one-step load acceptance.
- A one-year limited warranty covers all systems and components. Two-, five-, and ten-year extended warranties are also available.
- Generator features:
  - The brushless, rotating-field generator has broadrange reconnectability.
  - The permanent magnet-excited generator (PMG) provides superior short-circuit capability.
- Other features:
  - Controllers are available for all applications. See controller features inside.
  - Low coolant level shutdown prevents overheating.
  - Integral vibration isolation eliminates the need for under-unit vibration spring isolators.
  - An electronic, isochronous governor delivers precise frequency regulation.



## Generator Ratings

Model Series	Voltage Code	Voltage	Standby Amps	Phase	Hz	Generator Model	Standby Ratings, kW/kVA		Prime Power, kW/kVA	
							Nat. Gas	LP Gas	Nat. Gas	LP Gas
50GS60	01	120/240	165	3	60	4P8	55/69	55/69	50/63	50/63
50GS60	51	139/240	165	3	60	4P8	55/69	55/69	50/63	50/63
50GS60	51	127/220	180	3	60	4P8	55/69	55/69	50/63	50/63
50GS60	61	120/240	204	1	60	4P8	49/49	49/49	45/45	45/45
50GS60	71	277/480	83	3	60	4P8	55/69	55/69	50/63	50/63
50GS60	71	220/380	104	3	60	4P8	55/69	55/69	50/63	50/63
50GS60	81	120/208	191	3	60	4P8	55/69	55/69	50/63	50/63
50GS60	91	347/600	60	3	60	4P8	50/63	50/63	45/56	45/56
50GS50	01	110/220	148	3	50	4P8	45/56	45/56	41/51	41/51
50GS50	51	110/190	160	3	50	4P8	42/53	42/53	38/48	38/48
50GS50	61	110/220	191	1	50	4P10	42/42	42/42	38/38	38/38
50GS50	71	220/380	80	3	50	4P8	42/53	42/53	38/48	38/48
50GS50	71	230/400	76	3	50	4P10	42/53	42/53	38/48	38/48
50GS50	71	240/416	73	3	50	4P10	42/53	42/53	38/48	38/48
50GS50	81	120/208	146	3	50	4P10	42/53	42/53	38/48	38/48

RATINGS: Standby ratings are continuous for the duration of any power outage. No overload capacity is specified at this rating. Prime ratings are continuous per BS 5514, DIN 6271, ISO-3046, and IEC 34-1 with 10% overload capacity one hour in twelve hours. All single-phase units are rated at 1.0 power factor. All three-phase units are rated at 0.8 power factor. Contact the factory for ratings of city water-cooled and remote radiator models. Larger alternators may be used to meet special application requirements. Availability is subject to change without notice. The manufacturer of Spectrum products reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever. Contact your local Spectrum products distributor for availability. GENERAL GUIDELINES FOR DERATION: ALTITUDE: Derate 4% per 1000 ft. (305 m) elevation above 500 ft. (153 m). TEMPERATURE: Derate 1% per 10°F (5.5°C) temperature increase above 85°F (29°C).

# Alternator Specifications

Type .....	4-Pole, Rotating Field
Exciter type .....	Brushless, Permanent Magnet
Leads: quantity, type .....	12, Reconnectable
Voltage regulator .....	Solid State, Volts/Hz
Insulation:	NEMA MG1-1.66
Material .....	Class H
Temperature rise .....	130° C, Standby
Bearing: quantity, type .....	1, Sealed
Coupling .....	Flexible Disc
Amortisseur windings .....	Full
Voltage regulation, no load to full load ....	±2%
Unbalanced load capability	100% of Rated Standby Current
One-step load acceptance .....	100% of Rating
Peak motor starting kVA:	(35% dip for 480 V, 60 Hz and 380 V, 50 Hz)
4P8 .....	210 (60Hz), 145 (50Hz)
4P10 .....	255 (60Hz), 180 (50Hz)

- Complies with NEMA, IEEE, and ANSI standards for temperature rise.
- Sustains short-circuit current of up to 300% of rated current for up to 10 seconds.
- Sustains short-circuit current enabling downstream circuit breakers to trip without collapsing the generator field.
- Self-ventilation, drip-proof construction.
- Vacuum-impregnated windings with fungus-resistant epoxy varnish for dependability and long life.
- Superior voltage waveform from a two-thirds pitch stator and skewed rotor.
- Solid-state, volts-per-hertz voltage regulator with ±2% no-load to full-load regulation.
- Brushless alternator with brushless exciter for excellent load response.

## Application Data

### Engine

Engine Specifications	60 Hz	50 Hz
Manufacturer	Ford	
Engine: model, type	LSG-875, 4-Cycle, Natural Aspiration	
Cylinder arrangement	V-8	
Displacement, cu. in. (L)	460 (7.538)	
Bore and stroke, in. (mm)	4.36 (111.0) x 3.85 (98.0)	
Compression ratio	8.0:1	
Piston speed, ft./min. (m/sec.)	1155 (5.86)	962 (4.88)
Main bearings: quantity, type	5, Replaceable Insert	
Rated rpm	1800	1500
Max. power at rated rpm, HP (kW)	126 (94)	104 (76)
Cylinder head material	Cast Iron Alloy	
Piston type and material	Autothermic Aluminum Alloy	
Crankshaft material	Nodular Cast Iron	
Valves material	Forged Steel	
Governor: type, make/model	Electronic, Barber Colman	
Frequency regulation, no load to full load	Isochronous	
Frequency regulation, steady state	±0.5%	
Air cleaner type, all models	Dry	

### Exhaust

Exhaust System	60 Hz	50 Hz
Exhaust flow at rated kW, cfm (m <sup>3</sup> /min.)	550 (15.6)	430 (12.2)
Exhaust temperature at rated kW, dry exhaust, °F (°C)	1100 (593)	
Maximum allowable back pressure, in. Hg (kPa)	2.0 (6.8)	
Exhaust outlet size at hookup, in. (mm)	3.0 (76.2)	

### Engine Electrical

Engine Electrical System	60 Hz	50 Hz
Ignition system	Electronic, Breakerless	
Battery charging alternator:		
Ground (negative/positive) .....	Negative	
Volts (DC) .....	12	
Ampere rating .....	37	
Starter motor rated voltage (DC)	12	
Recommended battery cold cranking amps (CCA) rating for 0°F (-18°C)	630	
Batteries, quantity	1	
Battery voltage (DC)	12	
Rolling current at 32°F (0°C)	—	

### Fuel

Fuel System	60 Hz	50 Hz
Fuel type	LP Gas or Natural Gas Vapor	
Fuel supply line inlet	1 NPTF	
Natural gas/LPG fuel supply pressure oz./in. <sup>2</sup> (in. H <sub>2</sub> O)	4-6 (7-11)	

### Lubrication

Lubricating System	60 Hz	50 Hz
Type	Full Pressure	
Oil pan capacity, qts. (L)	8.0 (7.6)	
Oil pan capacity with filter, qts. (L)	9.0 (8.5)	
Oil filter: quantity, type	1, Cartridge	

# Application Data

## Cooling (Standard Radiator)

Cooling System	60 Hz	50 Hz
Ambient temperature, °F (°C)	115 (46)	
Engine jacket water capacity, gal. (L)	4.0 (15.1)	
Radiator system capacity, including engine, gal. (L)	6.9 (26.1)	
Engine jacket water flow, gpm (Lpm)	53 (201)	44 (167)
Heat rejected to cooling water at rated kW, dry exhaust, Btu/min.	2930	2440
Water pump type	Centrifugal	
Fan diameter, including blades, in. (mm)	23.6 (599)	
Fan, HP (kW)	4.5 (3.4)	2.6 (1.9)
Max. restriction of cooling air, intake and discharge side of radiator, in. H <sub>2</sub> O (kPa)	0.5 (0.125)	

## Cooling (Optional Systems)

High Ambient Radiator System	60 Hz	50 Hz
Ambient temperature, °F (°C)	122 (50)	
Engine jacket water capacity, gal. (L)	4.0 (15.1)	
Radiator system capacity, including engine, gal. (L)	7.5 (28.4)	
Engine jacket water flow, gpm (Lpm)	53 (201)	44 (167)
Heat rejected to cooling water at rated kW, dry exhaust, Btu/min.	2930	2440
Water pump type	Centrifugal	
Fan diameter, including blades, in. (mm)	23.6 (599)	
Fan, HP (kW)	4.5 (3.4)	2.6 (1.9)
Max. restriction of cooling air, intake and discharge side of rad., in. H <sub>2</sub> O (kPa)	0.5 (0.125)	

Remote Radiator System*	60 Hz	50 Hz
Exhaust manifold type	Dry	
Connection sizes:		
Water inlet, in. (mm) . . . . .	2.00 (51) ID Hose	
Water outlet, in. (mm) . . . . .	1.50 (38) ID Hose	
Static head allowable above engine, ft. (m) . . . . .	17.0 (4.32)	

\* Contact your local distributor for cooling system options and specifications based on your specific application.


City Water Cooling (CWC) System	60 Hz	50 Hz
Exhaust manifold type	Dry or Water Cooled	
System capacity, gal. (L)	6.6 (25.0)	
City water consumption, gpm (Lpm) at 50°F (10°C)	7.4 (28.0)	
Connection sizes:		
Water inlet, in. . . . .	0.75 NPT	
Water outlet, in. (mm) . . . . .	0.5 (12.7) NPT	

## Operation Requirements

Air Requirements	60 Hz	50 Hz
Radiator-cooled cooling air, cfm (m <sup>3</sup> /min.)	8400 (238)	6800 (193)
Cooling air required for gen. set when equipped with CWC or remote radiator, based on 25°F (14°C) rise and ambient temp. of 85°F (29°C), cfm (m <sup>3</sup> /min.)	4800 (135.9)	3900 (110.4)
Combustion air, cfm (m <sup>3</sup> /min.)	175 (5.0)	140 (4.0)
Heat rejected to ambient air:		
Engine, Btu/min. (kW) . . . . .	1680 (29.5)	1340 (23.6)
Generator, Btu/min. (kW) . . . . .	430 (7.6)	370 (6.5)

Fuel Consumption	60 Hz	50 Hz
<b>Natural Gas, cfm (m<sup>3</sup>/hr.) at % load</b>		
100%	920 (26.5)	720 (20.4)
75%	750 (21.2)	580 (16.4)
50%	580 (16.4)	450 (12.7)
25%	410 (11.6)	340 (9.6)
<b>LP Gas, cfm (m<sup>3</sup>/hr.) at % load</b>		
100%	400 (11.3)	320 (9.1)
75%	330 (9.3)	270 (7.6)
50%	270 (7.6)	210 (5.9)
25%	200 (5.7)	140 (4.0)

## Controllers



### Standard Controller

#### Microprocessor-Plus, 16-Light Controller

Audio/visual annunciation with NFPA-110, Level 1 capability  
 Microprocessor logic with AC meters and engine gauges  
 Compatible with 12-volt and 24-volt engine electrical systems  
 Remote start, prime power, and remote annunciation capability

### Optional Controllers

#### Digital Controller

Audio/visual annunciation with NFPA-110, Level 1 capability  
 Programmable microprocessor logic with digital display  
 Compatible with 12-volt and 24-volt engine electrical systems  
 Remote start, prime power, remote annunciation, and remote communication capability

#### Microprocessor-Plus, 7-Light Controller

Audio/visual annunciation with NFPA-110, Level 2 capability  
 Microprocessor logic with AC meters and engine gauges  
 Compatible with 12-volt and 24-volt engine electrical systems  
 Remote start, prime power, and remote annunciation capability

#### Basic Controller

Provides remote or automatic start with NFPA compliance  
 Uses single-light annunciation with basic control functions  
 Relay logic with three models—standard Basic, standard Basic with engine gauges, and expanded Basic with AC meters and engine gauges  
 Compatible with 12-volt engine electrical systems only

#### Manual Controller

Designed for prime power and mobile applications  
 Uses single-light annunciation with basic control functions  
 Relay logic with AC meters and engine gauges  
 Compatible with 12-volt engine electrical systems only

NOTE: See the respective controller spec sheet for additional controller features and accessories.



## Accessories

### Enclosed Unit

- Exhaust Silencer, Critical or Industrial
- Silencer Mounting Kit for Housing
- Tail Pipe and Rain Cap Kit
- Weather Housing

### Open Unit

- Exhaust Silencer, Critical or Industrial
- Flexible Exhaust Connector, Stainless Steel

### Cooling System

- Block Heater
- City Water Cooling
- High Ambient Radiator
- Radiator Duct Flange
- Remote Radiator Cooling

### Fuel System

- Automatic Changeover (natural gas to LP gas)
- Flexible Fuel Lines (LP gas)
- Gas Strainer
- LP Gas Liquid Withdrawal
- Manual Valve and Gas Solenoid Bypass
- Secondary Gas Solenoid Valve

### Electrical System

- Battery
- Battery Charger, Equalize/Float Type
- Battery Heater
- Battery Rack and Cables

### Engine and Generator

- Bus Bar Kits
- CSA Certification
- Generator Strip Heater
- Line Circuit Breaker
- Line Circuit Breaker with Shunt Trip
- NFPA 110 Literature
- Oil Drain Extension with Valve Kit
- Optional Generators
- Rated Power Factor Testing
- Rodent Guards
- Safeguard Breaker
- Skid End Caps
- Voltage Regulation, 1%
- Voltage Regulator Sensing, Three-Phase

### Maintenance

- General Maintenance Literature Kit
- Maintenance Kit (includes air, oil, and fuel filters)
- Overhaul Literature Kit

### Controller (Standard Controller)


- Common Failure Relay Kit
- Customer Connection Kit
- Dry Contact Kit (isolated alarm)
- Extension Wiring Harness for Remote Mounting of Controller
- FASTCHECK® Diagnostic Fault Detector
- Prealarm Sender Kit
- Remote Annunciator Panel
- Remote Audio/Visual Alarm Panel
- Remote Emergency Stop Kit
- Run Relay Kit

### Miscellaneous Accessories

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_

## WEIGHTS AND DIMENSIONS

Overall Size, L x W x H, in. (mm): 88.25 x 34.0 x 44.25  
 (2242 x 864 x 1124)  
 Weight (Radiator Model), wet lb. (kg): 1875 (851)



NOTE: This drawing is provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.

**DISTRIBUTED BY:**