



XQ Line Standard Rental Package



Sound Attenuated

XQ1750–1750 kW

XQ1250–1250 kW

XQ900–900 kW

Prime Power including 10% overload



FEATURES

■ CAT® GENERATOR SETS

Factory designed, certified prototype tested with torsional analysis. Production tested and delivered to you in a package that is ready to be connected to your fuel and power lines. Supported 100% by your Caterpillar dealer with warranty on parts and labor; extended warranty available in some areas.

■ RELIABLE, FUEL EFFICIENT DIESEL

The compact, four-stroke-cycle diesel engine combines durability with minimum weight while providing dependability and economy. The fuel system operates on a variety of fuels.

■ THE CATERPILLAR® GENERATOR

Single bearing, wye connected six lead permanent magnet excited, static regulated, brushless generator designed to match the performance and output characteristics of the Caterpillar diesel engine that drives it.

■ EXCLUSIVE CATERPILLAR® VOLTAGE REGULATOR

Three-phase sensing and Volts-per-Hertz regulation with excellent block loading and constant voltage in the normal operating range.

■ CATERPILLAR® COOLING SYSTEM

Sized compatible to rating with energy efficient fan and core.

■ ISO 9001 QUALITY SYSTEM STANDARD

Generator set designed and manufactured in conformance with ISO 9001 Quality System Standard; and generator set and components meet or exceed the following specifications: AS1359, AS2789, ABGSM TM3, BS4999, DIN6271, DIN6280, EGSA101P, JEM1359, IEC 34/1, ISO3046/1, ISO DIS 8528, NEMA MG1-22, 89/392 EEC.

■ CATERPILLAR® SWITCHGEAR

EMCP II based, semiautomatic paralleling components. Circuit breakers, bus bars, and connection panel ready to connect.

■ PLUG & PEAK SHAVE UTILITY CONVERSION PANELS (OPTIONAL)

The addition of the conversion panels will allow automatic or manual paralleling with a utility power source as a load management system with provisions for standby operation feeding an isolated load network. Easily installed in a few minutes by two people using four bolts and two quick connect type connectors per panel. Includes utility protective relays, loading controls, utility metering.

■ SOUND ATTENUATED, ISO CONTAINER

For ease of transportation and protection. Meets ISO/TC104, ANSI/MH5.1, and UIC Code 592-1. Meets 70 dBA at 50 ft or below per SAE J1074 measurement procedure.

STANDARD EQUIPMENT

Engine

Air cleaner with service indicator
 Batteries
 Filters
 fuel LH with service indicators
 lubricating oil
 Insulated muffler
 Jacket water heater
 Pump, fuel priming
 Radiator
 Service meter
 Standard 8-gauge instrument panel
 Sump pump

Generator

SR4 brushless, 480 volt
 PM excited
 Three-phase, with voltage regulator and
 space heater

Container

Side air intake louvers
 Bus bar access door
 Fuel tank w/gauge
 40-ft, 4732 L (1250 usable gal)
 Fuel/water separator
 24 VDC lighting
 Sound attenuated (72 dBA @ 50 ft)

Switchgear

Automatic start/stop with cycle cranking and
 cooldown timer
 Auxiliary power connections for
 jacket water heater, battery charger, space
 heaters
 Battery charger, heavy duty 20A
 Circuit breaker, manually operated
 Connection terminals, three-phase and neutral

CATERPILLAR® 3508, 3512, & 3516 ENGINE

V-8, V-12, & V-16, Four-Stroke-Cycle Diesel,
 1800 rpm
 Bore—mm (in) 170 (6.7)
 Stroke—mm (in) 190 (7.5)
 Displacement—L (cu in)
 V-8..... 34.5 (2105)
 V-12 51.8 (3158)
 V-16 69.0 (4210)
 Aspiration..... Turbocharged-Aftercooled

Cooling

Standard cooling provides 105° ambient at
 prime rating
 40-foot module, floor standing with EMCP II
 components
 2310A Load share governor

Enclosure

ISO hi cube container
 Lockable doors prevent vandalism or unsafe
 operating conditions
 Sound attenuation satisfies customer
 requirement for quiet rental units. Eliminates
 noise complaints.
 Stainless steel hardware and hinges provide
 superior rust corrosion protection.
 Vertical radiator and exhaust discharge plenum
 contribute to sound attenuation performance.
 Directs hot air and diffuses radiator discharge
 and exhaust gases upward, away from
 bystander and package. Allows for placement
 of power module next to a building or other
 obstruction that may restrict flow to the
 radiator.

OPTIONAL EQUIPMENT

Container

Roof air intake louvers

Switchgear (40 ft)

CIM, CCM, remote annunciation
 Circuit breaker, electrically operated
 Meters: power factor, KVAR, WM, W/WHM,
 synchroscope
 Paralleling: semiautomatic or fully automatic
 Protective Relays: 27, 59, 40, 46, 810, 81 V

CATERPILLAR® SR4 GENERATOR

Type Static regulated brushless PM excited
 Construction Single bearing, close coupled
 Three phase wye connected, six lead
 Insulation Class H – two extra dips and
 bakes on random wound units
 Enclosure Drip proof
 Alignment Pilot shaft
 Overspeed capability 130%
 Voltage regulator 3-phase sensing with
 Volts-per-Hertz
 Voltage regulation..... Less than ± 1%
 Voltage gain..... Adjustable to compensate for
 engine speed droop and line loss
 Wave form Less than 5% deviation
 TIF..... Less than 50
 THF Less than 3%

TECHNICAL DATA

3508, 3512, 3516 Generator Sets			XQ900	XQ1250	XQ1750
Rating Information	Engine 60 Hz – 1800 rpm	kW	3508	3512	3516
	Prime power rating (w/10% overload) @ 0.8PF with fan		900	1250	1750
	Voltage		480	480	480
	Aspiration		TA	TA	TA
Physical Factors – Package with undercarriage	Length	cm	1219	1219	1219
		in	480	480	480
	Width	cm	234	234	234
		in	92	92	92
	Height	cm	410	411	411
		in	150	162	162
	Shipping weight	kg	24 000	25 600	28 700
		lb	53 000	56 500	63 500
Lubrication & Cooling Systems	Engine lubricating oil capacity	L	250	348	470
		qts	264	368	497
	Engine coolant capacity w/radiator	L	285	318	440
	(with 50% glycol)	gal	75	84	116
Engine Performance Data @ Rated Conditions	Fuel tank capacity	L	4738	4738	4738
		gal	1250	1250	1250
	Fuel consumption prime (100% load) w/fan per ISO 3046/1 +55, -0% tolerance	L/Hr	255.9	333.6	504.7
		gph	67.6	88.2	133.4
	Fuel consumption (75% load) w/fan	L/Hr	195.6	248.2	378.1
		gph	51.7	65.6	99.9
	Fuel consumption (75% load) w/fan	L/Hr	134.0	175.0	264.6
		gph	35.4	46.3	69.9
	Deration:				
	Altitude – 3.0% per 305 m (1000 ft) above	m	900	1225	1375
		ft	2958	4019	4510
	Temperature – 1.9% per 5.5° C (10° F) above	° C	55	55	55
		° F	131	131	131
	at sea level or degree above standard ambient at altitude above 760 m (2500 ft).				
	Sound level – Prime +10% @ 16 m (50 ft) Log Average 4 pt.	dbA	68	69	70

DIMENSIONS



40 ft	L		H		W	
	cm	in	cm	in	cm	in
	1219	480	290	114	234	92

NOTE: The container meets or exceeds the following standards and regulations.

- ISO/TC 104 Requirements for Cargo Containers
- ANSI/MH5.1 Basic Requirements for Cargo Containers
- ANSI/MH5.1.1 Requirements for Closed Van Containers
- UIC CODE 592-1

The module must have support under the center when set on the ground.

3516 requires tri-axle chassis.

Maximum weight allowed on Interstate highways is 34 000 lb (rear axles). 3516 typically weighs 33 000 lb as shipped. The complete unit weighs 55 000 lb gross with chassis. Empty chassis weighs 6000 lb. These weights do not include tractor.

STANDARD CONTROLS

12 m (40 ft) containers (480 V/60 Hz, 400 V/50 Hz)

Floorstanding switchgear includes the following functions and features:

Electronic Modular Control Panel (EMCP II) Components

Generator Set Control (GSC)

Monitoring

Sequentially rotating, backlit LCD display of engine hours, engine rpm, DC battery voltage, oil pressure, and water temperature. Includes pushbutton to hold display on any single parameter.

Protection

Shutdowns:

Overspeed, overcrank, high water temperature, low oil pressure, and emergency stop. With LED indicator for each condition.

Alarms:

Low coolant level

AC Metering

Three-phase volts (L-L), amperes and frequency with phase select pushbutton, on backlit LCD. Metering accuracy is 0.5%.

Control

Automatic starting with field adjustable cycle crank, failure to start (overcrank), and cooldown timer.

Programming and Diagnostics

Includes field programmable set-points for engine control and monitoring variables and self diagnosis of EMCP II system component and wiring failures.

Alarm Module

Flashing LED warnings for: low coolant temperature, high coolant temperature (pre-alarm), low oil pressure (pre-alarm), engine control switch not in automatic, and low DC voltage. Includes alarm horn and acknowledge pushbutton.

Engine Control Switch

Snap action rotary switch, four-position – off/reset, automatic, manual, stop/cooldown. Off/reset for engine shutdown and resetting faults, automatic remote starting by customer contact closure, manual for local starting and manual paralleling, stop/cooldown for manual operation cooldown.

Alarm Acknowledge/Lamp Test Switch

Three-position, spring return to center switch for alarm acknowledge and lamp test of all discrete indicating lamps. Lamp test shall also sound the alarm horn.

Annunciation Circuits

Upon receipt of an alarm or shutdown condition, the horn shall sound and an LED shall flash. Upon acknowledgement from alarm acknowledge/lamp test switch, the horn shall be silenced and the lamp steadied. LED shall be extinguished when ECS is placed in the off/reset position if the alarm condition has been corrected. Circuits are recurring such that the LED shall flash and the horn sound, should another fault occur even prior to correction of the initial fault.

Emergency Stop Pushbutton

Mushroom head, twist to reset, causes engine shutdown

and tripping of the generator circuit breaker. Prevents engine starting when depressed.

Manual Paralleling

Controls consisting of reverse power relay, synchronizing lights, and switch. Reverse power condition causes tripping of the generator circuit breaker, immediate engine shutdown, flashing of indicating lamp, and sounding of alarm horn.

Circuit Breaker

Fix mounted, three-pole, manually operated, molded case circuit breaker with solid state trip unit for overload (time overcurrent) and fault (instantaneous) protection. Includes DC shunt trip coil activated on any generator set monitored fault. Circuit breaker is sized for full load capacity of the generator set at 0.8 power factor.

Load Share Governor

Electronic load sharing governor with speed adjust potentiometer, idle/rated switch, and isochronous/droop switch.

Voltage Regulator

Standard Caterpillar generator-mounted VR3 voltage regulator with voltage adjust rheostat mounted in the floor standing switchgear.

Current Transformers (3)

Five-ampere secondary with shorting terminal strips

Potential Transformers (3)

120VAC secondary with primary and secondary fuse protection, two connected to the generator side of the circuit breaker, one connected to the load side of the circuit breaker.

Bus Bars

Three-phase plus fully rated neutral bus bars with NEMA standard hole pattern for connection of customer load cables and generator cables. Bus bars are sized for full load capacity of the generator set at 0.8 power factor. Also includes ground bus, connected to the generator frame ground and container frame with holes for connection of field ground cable. Bus bars are accessible from outside of the power module via hinged, lockable cable access door.

Accessory Power

3500 Power Modules

Three 120VAC (60 Hz units) or 230VAC (50 Hz units) shore power connections for jacket water heaters, generator space heater, and battery charger.

Battery Charger

24VDC/20A battery charger with float/equalize modes and charging ammeter.

4160V or 3300V Power Modules

Similar to 480 V and 400 V units except for the following:

All bus bars are silver plated copper

Generator circuit breaker, three-pole, vacuum type, manually operated with 24VDC shunt trip. Sized for generator voltage and current ratings. Includes draw-out overcurrent relay, with instantaneous setting, ANSI device 50/51.